



9021H ARC 175LT



Input
Voltage



Moisture
Salt spray
Corrosion



MCU
Control
System



Generator
Friendly

FEATURES

- Digital display
- Built-in hot start, anti sticking and arc force
- Lift/Tig facility



EN 60974-1:2021 (LVD)
EN 60974-10:2021 (EMC)
2019/125/EC (EER)

SPECIFICATIONS

ARC 175LT

Power supply voltage (V)		230V ± 10%
Power frequency (Hz)		50/60
Effective input current (A)	MMA	TIG
Maximum (KVA)	37	27
Current adjustment range (A)	8.5	
Maximum no load voltage (V)	10 - 160	
Duty cycle (A) (40°C 10 min)	62	
	40% @ 160A	
	60% @ 135A	
	100% @ 105A	
Efficiency (%)		
Protection class	≥80	
Insulation class	IP23	
Cooling	H	
Electrode diameter (mm)	AF	
Electrode type	1.6 - 4.0	
Dimensions (mm)	6013, 7018 etc.	
Weight (kg)	362 x 148 x 280	
INCLUDES	4.5	

OPTIONAL



Earth Cable

EH32LE Electrode Lead



9807 Scratch Start Tig Package

9029 Carry Case



Scan For Manual

*All images used are for illustrative purposes only. Individual features such as sizes, fittings and other materials' colours may vary.