



9113H (Machine Only) TIG 250-3 LCD DC Tig



Easy
Arc
Striking



Pulse



Save Or
Load
Job



MCU
Contr
ol
Syste



Heavy
Duty
Cycle



4.3 in
480 x 272 px



Generator
Friendly



Tested
In
Production



Phase
Loss
Protection



Moisture²
Salt spray
Corrosion



12 PIN



35/70mm²
ø12mm

EN 60974-1:2021 (LVD)
EN 60974-10:2021 (EMC
2019/125/EC (EER)



SPECIFICATIONS

TIG 250-3 LCD

Power supply voltage (V)	3 - 400		
Power frequency (Hz)	50/60		
Effective current (A)	TI		MMA
Rated input current (A)	9		14.
Rated input power (KW)	12.8		1
	8.9		18.
Duty cycle (A) (40°C 10 min)		60% @ 250A	2
		100% @ 195A	12.
Welding current range (A)	5 - 250		10 - 250
No load voltage (V)			20.5
Efficiency (%)	73.5		
Power factor		89.5	
Protection class		0.68	
Cooling		IP21S	
Dimensions (mm)		AF	
Weight (kg)		550 x 190 x 360	
		13.6	

INCLUDES



Earth Cable



WE25/1212 Pin Plug (Pins 8 & 9)

OPTIONAL



9826HWired Pedal



Scan For Manual

*All images used are for illustrative purposes only. Individual features such as sizes, fittings and other materials' colours may vary.



ET26-12 Stealth Grip Torch	WP18AM Accessory Kit	D3595-1-1Tig Adaptor	EH32L Electrode Lead	WE25/12I Pin Plug (Pins 8 & 9)

					
ET20-12S Stealth Grip Torch	WP20A Accessory Kit	D3595-1-TTig Adaptor	EH32L Electrode Lead	WE25/12 Pin Plug (Pins 8 & 9)	9829/8" Quick Disconnect Adaptor Kit

					
ET18-12 Stealth Grip Torch	WP18A Accessory Kit	D3595-1-1Tig Adaptor	EH32L Electrode Lead	WE25/12 Pin Plug (Pins 8 & 9)	98293/8" Quick Disconnect Adaptor Kit *

*All images used are for illustrative purposes only. Individual features such as sizes, fittings and other materials' colours may vary. °Consists of 2 x M5028 IMPROPTANS® approved 150kVA three phase maximum amperage of this machine.