

9134H

MIG 200-1

2R Compact

1ph~230V
50/60Hz

Input Voltage

MCU
Contr
ol
Syste
m

MCU Contr ol Syste m

8.8.8
display

LED Display

ø300mm
(20kg)

ø300mm (20kg)

PROTEC
Tested
In
Production

Tested In Production

3
PROOF
Moisture
Salt spray
Corrosion

Moisture Salt spray Corrosion

Generator
Friendly

Generator Friendly

TOOLBOX



Comes with a toolbox storage compartment that provides a convenient and organised space for storing essential tools and accessories. This compartment helps keep items like welding tips, spares, gloves, wire brushes, and electrodes neatly arranged and easily accessible during welding projects, improving efficiency and ensuring that everything needed is on hand when required.

SPECIFICATIONS

MIG 200-1 2R COMPACT

Max input current (A)	43.
Effective current (A)	5
Input power (KW)	110
Welding current range (A)	30- 200
Welding voltage range (V)	15.5 - 24
No load voltage (V)	70
Duty cycle (A) (40°C 10 min)	20% @ 200A 60% @ 115A 100% @ 90A
Diameter (mm)	0.6 - 1.0
Cooling	AF
Protection class	IP21S
Dimensions (mm)	960 x 460 x 890
Weight (kg)	41.8

INCLUDES



*All images used are for illustrative purposes only. Individual features such as sizes, fittings and other materials' colours may vary.



Scan For Manual

EN 60974-1:2021 (LVD)

EN 60974-10:2021 (EMC)

2019/125/EC (EER)

CE