

Two Stage Fabmaster Elite Regulator 2 Gauge Argon 5 Bar– HL060009

Key Features:


- Unique economic colour coded PA Knob
- 2 years warranty.
- 300 bar service.
- Available in bottom & side entry.
- High contrast, easy to read gauges.
- Alloy bonnet for high strength.
- Manufactured under BS EN ISO 9001.
- Conforms to BS EN ISO 2503



Technical Data:

Specification	
Inlet Connection Arrangement	6 O'clock
Inlet Connection Length	80mm
Inlet Connection Size	BS341 No3
Outlet Connection Arrangement	3 O'clock
Outlet Connection Size	G3/8 RH
LP Relief Valve Arrangement	4 O'clock
HP Relief Valve Arrangement	7 O'clock
Inlet Pressure	230 Bar
Outlet Pressure setting	5 Bar
Weight	
Material	
Body	Brass
Bonnet	Zinc Alloy
Piston	
Seal	
Valve Seat	Modified PTFE
Filter	

Flow Data:



*FLOW TAKEN UNDER STANDARD WORKING TEMPERATURE OF 20°C ± 1.5°C USING OIL FREE BREATHABLE COMPRESSED AIR, WITH DIGITAL FLOW DEVICE (SERIAL NO.80765) CALIBRATED TO FULL SCALE PRESSURE 160PSIA WITH AN ACCURACY OF ± 0.5% OF FULL SCALE PRESSURE.