



Single Stage Fabmaster Elite Regulator 2 Gauge Nitrogen 10 Bar Side Entry – HL050075NITSE

Key Features


- Unique economic colour coded PA Knob
- 2 years warranty.
- 300 bar service.
- Available in bottom & side entry.
- High contrast, easy to ready gauges.
- Alloy bonnet for high strength.
- Manufactured under BS EN ISO 9001.
- Conforms to BS EN ISO 2503



Technical Data:

Specification	
Inlet Connection Arrangement	9 O'clock
Inlet Connection Length	110mm
Inlet Connection Size	BS341 No3
Outlet Connection Arrangement	4 O'clock
Outlet Connection Size	G3/8 RH
Relief Valve Arrangement	12 O'clock
Inlet Pressure	230 Bar
Outlet Pressure setting	10 Bar
Material	
Body	Brass
Bonnet	Zinc Alloy
Valve Seat	Modified PTFE

Flow Data:



*FLOW TAKEN UNDER STANDARD WORKING TEMPERATURE OF 25°C +/- 1.5°C USING OIL FREE BREATHABLE COMPRESSED AIR, WITH DIGITAL FLOW DEVICE (SERIAL NO.80763) CALIBRATED TO FULL SCALE PRESSURE 160PSIA WITH AN ACCURACY OF +/- 0.5%, OF FULL SCALE PRESSURE.