



Selected by Professionals

Stealth

WELDING MACHINES PRODUCT INFORMATION

| | | | | | | | | | |
|--------------------------------|------------------|----------|-------------------------|---|--------------------------|--------------------|-----------|---------------|--------------------|
| | | | | | | | | | |
| o 203mm (5kg) o 102mm (1kg) | 320 x 480 TFT | Synergic | Power Factor Correction | Moisture ✓ Salt spray ✓ Corrosion ✓ | Voltage Reduction Device | MCU control system | Spool gun | Input voltage | Generator friendly |

9005H

DIGI-MIG 200 LCD PFC

Multiprocess – 110V/230V

PRODUCT SUMMARY

A versatile portable compact inverter welder equipped with IGBT components, multi process capabilities and LCD displaying 260,000 true colours. Multiple advantages such as energy saving and wider input voltage.

FEATURES

- Power factor more than 0.99
- Works with 110V and 230V
- Capable of loading up to 5kg spool
- Waveform control for added stability of the arc – even at low currents
- Equipped with temperature, voltage and current sensors for high protection

OPTIONAL EXTRAS

- 9862H** 150A Air-Cooled Tig Kit for 9005H
- EH52LD** 200A Electrode Holder c/w 35-50 Dinse x 3m
- 9005H-99H** Feed Roll U Type 0.8-1.0mm Aluminium
- 9005H-99C** Feed Roll U type 0.8-1.0mm Flux Cored
- M1513-3** Aluminium Liner 1.0-1.2mm Wire x 3m



SPECIFICATIONS

| | | | | | | |
|-------------------------------|-------------------------------------|------------|------------|--------------------|------------|------------|
| Input power voltage (V) | 110/230±10% | | | | | |
| Frequency (Hz) | 50/60 | | | | | |
| | MIG | TIG | MMA | | | |
| Effective current – 110V | 23.4 | 17.7 | 17.7 | | | |
| Effective current – 230V | 17.7 | 13.9 | 20.2 | | | |
| | MIG | TIG | MMA | MIG | TIG | MMA |
| Rated input current (A) | 37 | 28 | 28 | 28 | 22 | 32 |
| Duty cycle (A) (40°C 10 min) | 40% @ 140 | 40% @ 100 | 40% @ 200 | | | |
| | 60% @ 115 | | 60% @ 85 | 60% @ 165 | | |
| | 100% @ 90 | 100% @ 65 | 100% @ 130 | | | |
| No load voltage – limited (V) | 67 (MIG) 14 (TIG/MMA) | | | | | |
| Welding current range (A) | 25~140 (MIG 110V) | | | 25~200A (MIG 230V) | | |
| Welding voltage range (V) | 10~21 (MIG 110V) | | | 10~27V (MIG 230V) | | |
| Efficiency (%) | 80 | | | | | |
| Power factor | 0.99 | | | | | |
| Insulation class | H | | | | | |
| Protection class | IP23 | | | | | |
| Cooling | Air | | | | | |
| Overall dimensions (mm) | 560 x 220 x 410 | | | | | |
| Weight (kg) | 15.5 | | | | | |
| Accessories included | 3m Argon hose, 3m earth return lead | | | | | |



Supplied with **2068 ARGON/CO₂ PRESSURE REGULATOR**
Single Stage 2g – Argon/CO₂ Regulator – 30 lpm

and **M25-3 MIG TORCH**
3m Bladeswitch
c/w Euro Fitting

