






Selected by Professionals

Stealth

WELDING MACHINES PRODUCT INFORMATION

- 
 MCU Control System
- 
 Input Voltage
110-230V
50/60HZ
- 
 Dual Pulse
- 
 Optional Foot Control
- 
 Optional Potentiometer Remote Control Torch
- 
 Power Factor Correction
0.99
- 
 Optional Up/Down Remote Control
- 
 Welding at Extra Low Current
- 
 Generator Friendly

9010H DIGI-TIG 200 DC PULSE PFC MV

Multi Voltage – 110V-230V

PRODUCT SUMMARY

A Dual Voltage DC 200 Amp Tig welder with pulse welding and PFC. Lightweight and supplied in a carry case. Ideal for TIG weld Mild Steel and Stainless.

FEATURES

- Tig/MMA functions
- Full digital control panel
- Slope in / Slope out
- 2T - 4T trigger function
- 0.5 - 200 pulse frequency

OPTIONAL EXTRAS

- 9821H** Air-Cooled Tig package
- 9822H** Water-Cooled Tig package
- ET17-125Z** Torch
- D3595-1-1** Tig Adaptor



- Carry Case Supplied

USE OUR SUPER 6 A18 TIG RODS



- 7362** 1.6mm
- 7363** 2.4mm



| SPECIFICATIONS | | | | |
|------------------------------------|-------------------------------|------------|------------|------------|
| Input power voltage | 110±10% | | 230±10% | |
| | TIG | MMA | TIG | MMA |
| Effective input current (A) | 10 | 18 | 10 | 13 |
| Maximum (KVA) | 3.6 | | 5.4 | |
| Input voltage frequency (Hz) | 50/60 | | | |
| No load voltage (V) | 65 | | | |
| Current adjustment range (A) | 5-110 | | 5-180 | |
| Duty cycle (A) (40°C 10 min) | 35% @ 110 | 30% @ 110 | 35% @ 180 | 25% @ 180 |
| | 60% @ 85 | 60% @ 80 | 60% @ 140 | 60% @ 120 |
| | 100% @ 65 | 100% @ 65 | 100% @ 110 | 100% @ 100 |
| Protection class | Ip23 | | | |
| Insulation class | H | | | |
| Up slope/Down slope (S) | 0-10 | | | |
| Pulse width range (%) | 5-95 | | | |
| Post-gas time adjustment range (S) | 0-10 | | | |
| Power factor | 0.99 | | | |
| Overall dimensions (mm) | 465 x 146 x 278 | | | |
| Weight (kg) | 7.5 | | | |
| Accessories included | 3m Argon hose + Amphenol plug | | | |

